

# QUESTED VH3208

Mid-Field/Main System Passive Reference Monitor



One of the most commonplace monitors in top studios, the VH3208 is Quested's smallest passive 3-way monitor.

A 3-way, dual bass driver design ensures that the VH3208 has the benefit of unsurpassed clarity in the mid-range together with an accurate, solid bottom.

The three sections of the audiophile quality passive filter networks are independently accessible on the triple pair binding post tray making tri-wiring, or tri-amping a possibility.\*

We recommend a Quested AP1550-2 amplifier for use with the VH3208.

Size (WxHxD)	485(w) x 612(h) x 324(d) mm
Weight	38 kgs
Drivers	Bass: 2 x 200 mm (8") cone Mid: 1 x 75mm (3") soft dome HF: 1 x 28mm (1.125") soft dome
Maximum SPL	115dB(C)
Sensitivity	92dB at 1 watt at 1 meter
Frequency Response	45Hz - 20kHz +/-2 dB
Input Connectors	Triple-pair gold plated binding posts, accepting 4mm banana plugs or bare wire
Nomina Impedance	8 ohm
Crossovers	Low/Mid - 90Hz, Mid/High - 2.8 kHz
Power requirements	Amplifier rated at 200 -700 watts RMS at 8 hms

\*Note: Not to be confused with 2 & 3-way Active which require the use of an external electronic crossover.

The VH3208 is not suitable for operation in "Active" mode.


## Quested Monitoring Systems

Unit 8, Kingsgate, Heathpark, Honiton, Devon EX14 1YG, UK - T +44 (0)1404 41500 - E [info@quested.com](mailto:info@quested.com)

[www.quested.com](http://www.quested.com)



EAT



SLEEP



MIX

# QUESTED VH3208

Mid-Field/Main System Passive Reference Monitor



One of the most commonplace monitors in top studios, the VH3208 is Quested's smallest passive 3-way monitor.

A 3-way, dual bass driver design ensures that the VH3208 has the benefit of unsurpassed clarity in the mid-range together with an accurate, solid bottom.

The three sections of the audiophile quality passive filter networks are independently accessible on the triple pair binding post tray making tri-wiring, or tri-amping a possibility.\*

We recommend a Quested AP1300 amplifier for use with the VH3208.

Size (WxHxD)	485(w) x 612(h) x 324(d) mm
Weight	38 kgs
Drivers	Bass: 2 x 200 mm (8") cone Mid: 1 x 75mm (3") soft dome HF: 1 x 28mm (1.125") soft dome
Maximum SPL	115dB(C)
Sensitivity	92dB at 1 watt at 1 meter
Frequency Response	45Hz - 20kHz +/-2 dB
Input Connectors	Triple-pair gold plated binding posts, accepting 4mm banana plugs or bare wire
Nomina Impedance	8 ohm
Crossovers	Low/Mid - 90Hz, Mid/High - 2.8 kHz
Power requirements	Amplifier rated at 200 -700 watts RMS at 8 hms

\*Note: Not to be confused with 2 & 3-way Active which require the use of an external electronic crossover.

The VH3208 is not suitable for operation in "Active" mode.

## Quested Monitoring Systems

Unit 8, Kingsgate, Heathpark, Honiton, Devon EX14 1YG, UK - T +44 (0)1404 41500 - E [info@quested.com](mailto:info@quested.com)

[www.quested.com](http://www.quested.com)



EAT



SLEEP



MIX